

호칭	골지름 (암나사)					2A Max	2A Mean	2B Max	2B Mean	4 산0.242-.152 6 산0.195-.116 8 산0.153-.096
	외경 3A	외경 3A Max	접촉 높이	드릴경 75%	피치					
5/16-20	7.938	8.133	0.687	6.699	1.27	7.907		8.180		1 5/16-12
5/16-28	7.938	8.067	0.491	7.053	0.907	7.912		8.108		1 5/16-16
3/8-20	9.525	9.720	0.687	8.287	1.27	9.495		9.769		1 5/16-20
3/8-28	9.525	9.654	0.491	8.641	0.907	9.497		9.694		1 5/16-28
7/16-16	11.113	11.366	0.859	9.565	1.588	11.077		11.419		1 3/8-8
7/16-32	11.113	11.220	0.430	10.339	0.794	11.087		11.260		1 3/8-16
1/2-16	12.700	12.954	0.859	11.152	1.588	12.664		13.007		1 3/8-20
1/2-32	12.700	12.805	0.430	11.926	0.794	12.675		12.847		1 3/8-28
9/16-16	14.288	14.540	0.859	12.74	1.588	14.252		14.595		1 7/16-6
9/16-20	14.288	14.480	0.687	13.049	12.7	14.254		14.530		1 7/16-8
9/16-28	14.288	14.413	0.491	13.403	0.907	14.260		14.456		1 7/16-12
9/16-32	14.288	14.393	0.430	13.514	0.794	14.260		14.431		1 7/16-16
5/8-12	15.875	16.229	1.146	13.811	2.117	15.834		16.292		1 7/16-20
5/8-16	15.875	16.127	0.859	14.327	1.588	15.839		16.182		1 7/16-28
5/8-20	15.875	16.067	0.687	14.637	1.270	15.842		16.117		1 1/2-8
5/8-28	15.875	16.000	0.491	14.991	0.907	15.847		16.044		1 1/2-16
5/8-32	15.875	15.978	0.430	15.101	0.794	15.847		16.020		1 1/2-20
11/16-12	17.463	17.816	1.146	15.399	2.117	17.422		17.879		1 1/2-28
11/16-16	17.463	17.714	0.859	15.915	1.588	17.427		17.770		1 9/16-6
11/16-20	17.463	17.654	0.687	16.224	1.270	17.429		17.705		1 9/16-8
11/16-28	17.463	17.587	0.491	16.578	0.907	17.435		17.631		1 9/16-12
11/16-32	17.463	17.566	0.430	16.689	0.794	17.435		17.607		1 9/16-16
3/4-12	19.050	19.403	1.146	16.986	2.117	19.007		19.464		1 9/16-20
3/4-28	19.050	19.174	0.491	18.166	0.907	19.020		19.216		1 5/8-6
3/4-32	19.050	19.152	0.43	18.276	0.794	19.022		19.195		1 5/8-8
13/16-12	20.638	20.990	1.146	18.574	2.117	20.594		21.052		1 5/8-12
13/16-16	20.638	20.888	0.859	19.090	1.588	20.599		20.943		1 5/8-16
13/16-28	20.638	20.760	0.491	19.753	0.907	20.607		20.804		1 5/8-20
13/16-32	20.638	20.740	0.430	19.864	0.794	20.610		20.782		1 11/16-6
7/8-12	22.225	22.577	1.146	20.161	2.117	22.182		22.640		1 11/16-8
7/8-16	22.225	22.475	0.859	20.677	1.588	22.187		22.531		1 11/16-12
7/8-28	22.225	22.347	0.491	21.341	0.907	22.195		22.391		1 11/16-16
7/8-32	22.225	22.326	0.430	21.451	0.794	22.197		22.369		1 11/16-20
15/16-12	23.813	24.164	1.146	21.749	2.117	23.769		24.227		1 3/4-6
15/16-16	23.813	24.062	0.859	22.265	1.588	23.774		24.118		1 3/4-8
15/16-28	23.813	23.934	0.491	22.928	0.907	23.782		23.979		1 3/4-12
15/16-32	23.813	23.912	0.430	23.039	0.794	23.785		23.956		1 3/4-16
1-16	25.4	25.649	0.859	23.852	1.588	25.362		25.706		1 3/4-20
1-28	25.4	25.552	0.491	24.516	0.907	25.37		25.566		1 7/8-6
1-32	25.4	25.499	0.430	24.626	0.794	25.372		25.544		1 7/8-8
1 1/16-8	26.987	27.543	1.719	23.892	3.175	26.937		27.622		1 7/8-12
1 1/16-12	26.987	27.338	1.146	24.924	2.117	26.944		27.402		1 7/8-16
1 1/16-16	26.987	27.236	0.859	25.440	1.588	26.949		27.293		1 7/8-20
1 1/16-20	26.987	27.175	0.687	25.749	1.27	26.952		27.227		1 15/16-6
1 1/16-28	26.987	27.108	0.491	26.103	0.907	26.957		27.154		1 15/16-8
1 1/8-8	28.575	29.130	1.719	25.479	3.175	28.522		29.208		1 15/16-12
1 1/8-16	28.575	28.823	0.859	27.027	1.588	28.537		28.881		1 15/16-16
1 1/8-20	28.575	28.762	0.687	27.337	1.27	28.539		28.815		1 15/16-20
1 1/8-28	28.575	28.695	0.491	27.691	0.907	28.545		28.741		2-6
1 3/16-8	30.162	30.715	1.719	27.067	3.175	30.109		30.796		2-8
1 3/16-12	30.162	30.512	1.146	28.099	2.117	30.119		30.577		2-12
1 3/16-16	30.162	30.410	0.859	28.615	1.588	30.124		30.468		2-16
1 3/16-20	30.162	30.349	0.687	28.924	1.27	30.127		30.402		2-20
1 3/16-28	30.162	30.282	0.491	29.789	0.907	30.132		30.329		2 1/8-6
1 1/4-8	31.750	32.302	1.719	28.645	3.175	31.697		32.383		2 1/8-8
1 1/4-16	31.750	31.997	0.859	30.202	1.588	31.712		32.056		2 1/8-12
1 1/4-20	31.750	31.936	0.687	30.512	1.27	31.714		31.990		2 1/8-16
1 1/4-28	31.750	31.869	0.491	30.866	0.907	31.720		31.916		2 1/8-20
1 5/16-8	33.337	33.889	1.719	30.242	3.175	33.284		33.971		2 1/4-6